



**WACKER
NEUSON**
all it takes!



High frequency internal vibrator with integrated converter IRFU 45/120/10

5100008935

[Home](#) >> [Catalog](#) >> [Products](#) >> [Concrete Technology](#) >> [Internal Vibrators](#) >> [High Frequency Internal Vibrators with integrated converter](#) >> [High frequency internal vibrator with integrated converter IRFU 45/120/10](#)

High frequency internal vibrator with integrated converter IRFU 45/120/10

Material number 5100008935



Electric internal vibrator with integrated frequency inverter for concrete compaction. Protection hose length of 10 meters. With integrated personal protection switch (Bodyguard™).

Product details

High frequency internal vibrator, designed for the toughest application conditions

- Integrated frequency inverter, therefore two pieces of equipment in one for convenient handling and compensation for fluctuating input voltages. No external inverter required.
- Power cable outfitted with Bodyguard™ (shutdown of the equipment in cases of emergency within 3 msec.) to protect the operator from electric shock if the electric power supply is insufficiently secured.
- Complete potted electronic components for a long service life
- Wear resistant vibrator head made of steel, completely induction hardened
- Repairable vibrator head (exchange of individual components)
- Ergonomically shaped switch box
- RPM-stable, powerful electric motor designed, developed and produced in-house - Made in Germany
- With integrated thermal overload protection breaker
- Power cable made of sturdy, flexible rubber

Comes with

- Internal vibrator
- Operator's manual

Technical specifications

High frequency internal vibrator with integrated converter IRFU 45/120/10

THERMAL - OUTPUT DETAILS

Overheat limit activation	150 °C
---------------------------	--------

ELECTRICAL - OUTPUT DETAILS

Nominal current	9,60 A
Nominal voltage	110 - 130 V
Nominal frequency	50 - 60 Hz
Nominal power [P]	0,88 KW
Phase	1 ~

ENVIRONMENT DATA

Protection class	I / Protective earthing
Storage temperature range	-20 - 60 °C
Degree of protection	IP67
Sound level LpA	79,0 dB(A)
Measuring method LpA	LPA1m
Sound level LpA (Standard)	DIN EN ISO 11201
Operating temperature range	-10 - 40 °C
Vibration total value ahv	2,5 m/s ²
Vibration value ahv (Standard)	DIN EN ISO 20643
Uncertainty in measurement HAV	0,5 m/s ²

MECHANICAL - OUTPUT DETAILS

Amplitude at air	2,30 mm
Vibrations	12.000 1/min
Vibrations (Hz)	200 Hz

OPERATING FLUIDS

Oil volume	0,010 l
Oil specification	Klüberoil 4UH1-46N

ELECTRICAL SYSTEM

Breaker Switch On/Off	yes
Integrated transformer	yes
Light cone	15,0 m
Length Cable	15,00 m
Kind of plug	CEE-Plug 2P+E 16A 110V 4H

MECHANICAL DETAILS

Length Hose	10,00 m
Length Head	382 mm
External diameter hose	31 mm
Head diameter/-diagonal	45 mm
Head design	round
Weight	20,90 kg
Rubber cap	no

MOTOR

Motor type	asynchronous motor
------------	--------------------

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE